

DIVYOL ECO4 SAE 20W40 API CF / SF High Performance Gas Engine Oil

Applications

Divyol ECO4 SAE 20W40 is a specially formulated lubricant designed for diesel engines in heavy duty applications. It is ideal for relatively older diesel engines, large or small, non-turbocharged or turbocharged diesel engines and recommended for use in heavy duty commercial vehicles, light commercial vehicles, multi-utility vehicles, tractors, three wheelers, gensets, etc. with high speed naturally aspirated or turbo charged diesel engines. It is especially good for driving in hilly regions.

Specifications

Divyol ECO4 SAE 20W40 meets and exceeds API CF / SF specifications. The oil is fortified with additives for high detergent, dispersant and anti-oxidation actions.

Pack Sizes

1 L, 5 L, 7.5 L, 10 L, 15 L, 26 L, 50 L, 210 L.

Advantages

Divyol ECO4 SAE 20W40 provides outstanding protection against wear, corrosion, oil degradation and thickening. It gives enhance protection especially to critical engine parts like cylinder liner, piston rings, valve, cams etc. It also ensures excellent oxidation stability over wide range of temperatures and extended oil drain intervals.

Sr. No.	Characteristics	Test Method	UOM	Specifications
1	Appearance	Visual	-	Bright and clear
2	Colour, max.	ASTM D 1500	-	Natural
3	Specific gravity at 29.5 °C	ASTM D 1298	-	To report
4	Kinematic viscosity at 100 °C	ASTM D 445	cSt	12.5 – 16.3
5	Viscosity index, min.	ASTM D 2270	-	110
6	Flash point, min. COC	ASTM D 92	°C	220
7	TBN, min.	ASTM D 2896	mg KOH/g of oil	6
8	Pour point, max.	ASTM D 97	°C	-9

Disclaimer: Gandhar makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.

Storage: All packages should be stored under cover. Avoid direct sun light or heat. Keep the container in closed / properly sealed condition to avoid contamination.

Handling, Health & safety: As with all the products, please take care to avoid environmental contamination when disposing of this product. Do not dispose the used oil to soil, drains and water. Avoid contact with skin and eyes. After skin contact wash with soap and water. This product should not cause any health problems when used in the applications suggested and the guidance provided in the safety data sheet (SDS) is followed.