

DIVYOL FILTER TESTING OIL

Applications:

Divyol Filter Testing Oil is specially formulated using highly refined base stocks and premium additives to produce a reference fluid for diesel fuel pumps and injectors. It can be used to calibrate flow test and flush diesel fuel injection system pumps, injector nozzles as also for automotive filter testing.

Advantages:

Divyol Filter Testing Oil has a special additive system to protect all the components of a fuel injection system against corrosion and prevents deposit formation. It has excellent anti-wear and anti-foaming properties besides low cloud point and pour point. It is a highly saturated composition offering close control of viscosity, low volatility and high flash point. It is colourless and odourless.

Typical properties:

Sr. No.	Characteristics	Test Method	Divyol Filter Testing Oil
1	Appearance	Visual	Bright and Clear
2	Kinematic viscosity at 40 °C	ASTM D 445	3.8 – 4.2
3	Flash point, COC, °C, min.	ASTM D 92	100
4	Pour point, °C, max.	ASTM D 97	-3
5	Copper corrosion, 100 °C for 3 hrs.	ASTM D 130	1a
6	Dielectric strength, min.	IS:6792	30

The above properties are typical values and do not constitute specification of the product.

Disclaimer: Gandhar makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.