

DIVYOL HYDRAULIC OIL 30W Construction Equipment Oil

Specially designed for equipment deployed in the construction and mining sector

Applications

Smooth operation of wide range of heavy duty and static hydraulic applications.

- Ideal for heavy duty applications like bulldozers, excavators, diggers and cranes
- Formulated using high viscosity-index paraffinic base stocks and premium performance additives

Specifications

Meets and exceeds OEM specs.

- Meets the anti-wear specifications of the leading equipment manufacturers
- Performance level : Caterpillar TO-2
- Pack sizes : 26 L, 50 L, 210 L

Advantages

Get the most from your machinery and extend its performance.

- Superior protection to the equipment against wear, corrosion and foaming
- Helps maintain a clean engine
- Better fuel efficiency at an optimum cost
- Effective lubrication viscosity at elevated temperatures

Sr. No.	Characteristics	Test Method	UOM	Specifications
1	Appearance	Visual	-	Bright and clear
2	Colour, max.	ASTM D 1500	-	2.5
3	Specific gravity at 29.5 °C	ASTM D 1298	-	To report
4	Kinematic viscosity at 100 °C	ASTM D 445	cSt	10 – 12.5
	Viscosity index, min.	ASTM D 2270	-	110
5	Flash point, min. (COC)	ASTM D 92	°C	210
6	Pour point, max.	ASTM D 97	°C	-15

Disclaimer: Gandhar makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.

Storage: All packages should be stored under cover. Avoid direct sun light or heat. Keep the container in closed / properly sealed condition to avoid contamination.

Handling, Health & safety: As with all the products, please take care to avoid environmental contamination when disposing of this product. Do not dispose the used oil to soil, drains and water. Avoid contact with skin and eyes. After skin contact wash with soap and water. This product should not cause any health problems when used in the applications suggested and the guidance provided in the safety data sheet (SDS) is followed.