



DIVYOL MARINE ENGINE OILS (SAE 50) MDE 560 / MDE 565 / MDE 570

Applications:

Divyol Marine Engine Oils (SAE 50) are high TBN oils specifically formulated for the cylinder lubrication of two-stroke, slow speed, cross head engines. They are available with TBN of 60, 65 and 70 and can be used with residual fuel.

Advantages:

Divyol Marine Engine Oils (SAE 50) have a unique patented chemistry designed for optimum performance including a host of benefits. It is a premium single oil solution designed to lubricate 2-stroke engines using fuels and is validated for dual fuel operation. It possesses excellent anti-wear properties which extends the service life of components. It neutralizes combustion acid, has very good film strength and keeps engine parts clean and without harmful deposits.

Typical properties:

Sr. No.	Characteristics	Test Method	Divyol Marine Engine Oils		
			MDE 560	MDE 565	MDE 570
1	Appearance	Visual	Bright and clear	Bright and clear	Bright and clear
2	Kinematic viscosity at 100 °C, cSt	ASTM D 445	16.3 – 21.5	16.3 – 21.5	16.3 – 21.5
3	Viscosity index	ASTM D 2270	95	95	95
4	Flash point, °C	ASTM D 92	>210	>210	>210
5	Pour point, °C	ASTM D 97	≤6	≤6	≤6
6	Sulphated ash	ASTM 874	7.0	7.0	7.0
7	TBN (Total Base No), mg KOH/g	ASTM D 2896	60	65	70

The above properties are typical values and do not constitute specification of the product.

Disclaimer: Gandhar makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.

