

## DIVYOL POWER TRANS C3 / C4 SAE 10 AND 30

### Hydraulic Transmission Fluids

#### Applications

Divyol Power Trans C3 / C4 SAE 10 and 30 are heavy duty automatic transmission oils, specially developed for on and off-highway requirements including earth-moving machinery. These oils are ideal for heavy duty and power shift transmissions.

#### Specifications

Divyol Power Trans C3 / C4 SAE 10 and 30 transmission oils are formulated with superior quality hydro finished base oils and additives. They meet and exceed leading OEM specifications including Type C-4 of Allison Transmission Division of General Motors, USA, and Caterpillar TO-2.

#### Pack Sizes

500 ml, 1 L, 5 L, 26 L, 50 L, 210 L.

#### Advantages

Divyol Power Trans C3 / C4 SAE 10 and 30 p transmission oils have the required friction characteristics for a smooth transmission performance. These oils ensure excellent oxidation stability and retain fluidity even at low temperatures. They provide effective protection against corrosion and wear, especially to critical and complex transmission components.

| Sr. No. | Characteristics               | Test Method | UOM | Specifications             |                            |
|---------|-------------------------------|-------------|-----|----------------------------|----------------------------|
|         |                               |             |     | Power Trans C3 / C4 SAE 10 | Power Trans C3 / C4 SAE 30 |
| 1       | Appearance                    | Visual      | -   | Bright and clear           | Bright and clear           |
| 2       | Colour, max.                  | ASTM D 1500 | -   | Natural                    | Natural                    |
| 3       | Specific gravity at 29.5 °C   | ASTM D 1298 | -   | To report                  | To report                  |
| 4       | Kinematic viscosity at 100 °C | ASTM D 445  | cSt | 5.6 – 7.4                  | 9.3 – 12.5                 |
| 5       | Viscosity index, min.         | ASTM D 2270 | -   | 95                         | 95                         |
| 6       | Flash point, min. COC         | ASTM D 92   | °C  | 190                        | 200                        |
| 7       | Pour point, max.              | ASTM D 97   | °C  | -21                        | -15                        |

Disclaimer: Gandhar makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.

Storage: All packages should be stored under cover. Avoid direct sun light or heat. Keep the container in closed / properly sealed condition to avoid contamination.

Handling, Health & safety: As with all the products, please take care to avoid environmental contamination when disposing of this product. Do not dispose the used oil to soil, drains and water. Avoid contact with skin and eyes. After skin contact wash with soap and water. This product should not cause any health problems when used in the applications suggested and the guidance provided in the safety data sheet (SDS) is followed.