

## DIVYOL SPINE EP 90 API GL4

### High Performance Gear Oil

#### Applications

Divyol Spine EP 90 is a high performance gear oil specially developed for cars, buses and off highway equipment. It is suitable for a wide range of gear units: with normal, bevel and helical gear designs, including synchromesh manual gearboxes. It also improves efficiency of transmissions and axles under moderately severe load and pressure conditions.

#### Specifications

Divyol Spine EP 90 meets and exceeds OEM standards for cars, vans and commercial vehicles, including API GL4, BIS 1118-92 RA 2011 (EP TYPE-GL4) and US MIL-L-2105.

#### Pack Sizes

500 ml, 1 L, 5 L, 10 L, 20 L, 26 L, 50 L, 210 L.

#### Advantages

Divyol Spine EP 90 helps extend the service life of gears by providing excellent corrosion resistance leading to significant reduction in maintenance costs and noise level. It facilitates high load carrying capacity, even at high speeds.

Sr. No.	Characteristics	Test Method	UOM	Divyol Spine EP 90
1	Appearance	Visual	-	Bright and clear
2	Colour, max.	ASTM D 1500	-	5
3	Specific gravity at 29.5 °C	ASTM D 1298	-	To report
4	Kinematic viscosity at 100 °C	ASTM D 445	cSt	14 – 18
5	Viscosity index, min.	ASTM D 2270	-	90
6	Flash point, min. COC	ASTM D 92	°C	195
7	Pour point, max.	ASTM D 97	°C	-6

Disclaimer: Gandhar makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.

Storage: All packages should be stored under cover. Avoid direct sun light or heat. Keep the container in closed / properly sealed condition to avoid contamination.

Handling, Health & safety: As with all the products, please take care to avoid environmental contamination when disposing of this product. Do not dispose the used oil to soil, drains and water. Avoid contact with skin and eyes. After skin contact wash with soap and water. This product should not cause any health problems when used in the applications suggested and the guidance provided in the safety data sheet (SDS) is followed.