

DIVYOL TQX TYPE: DEXRON III E

Hydraulic Transmission Fluid

Applications

Divyol TQX DEXRON III E is a superior quality transmission and power steering oil developed for modern automatic transmission cars, especially passenger cars and commercial vehicles. It is ideal for automatic transmission systems, power steering, hydraulic systems and torque converters.

Specifications

Divyol TQX DEXRON III E automatic transmission fluid is formulated using superior quality hydro finished base oils and additives. It meets and exceeds leading OEM specifications and conforms to performance level of vehicles requiring Dexron III fluid.

Pack Sizes

500 ml, 1 L, 5 L, 26 L, 50 L, 210 L.

Advantages

Divyol TQX DEXRON III E automatic transmission fluid has the required friction characteristics for a smooth transmission performance. It retains good fluidity even at low temperatures. It also has excellent anti-oxidation, dispersancy, anti-wear and de-foaming properties. These qualities help extend the service life of seal components and ensure complete and effective protection, especially to the critical and complex transmission components.

Sr. No.	Characteristics	Test Method	UOM	Specifications
1	Appearance	Visual	-	Bright and clear
2	Colour, max.	ASTM D 1500	-	Red
3	Specific gravity at 29.5 °C	ASTM D 1298	-	To report
4	Kinematic viscosity at 100 °C	ASTM D 445	cSt	6.8 – 8.4
5	Viscosity index, min.	ASTM D 2270	-	160
6	Flash point, min. COC	ASTM D 92	°C	180
7	Pour point, max.	ASTM D 97	°C	-39

Disclaimer: Gandhar makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.

Storage: All packages should be stored under cover. Avoid direct sun light or heat. Keep the container in closed / properly sealed condition to avoid contamination.

Handling, Health & safety: As with all the products, please take care to avoid environmental contamination when disposing of this product. Do not dispose the used oil to soil, drains and water. Avoid contact with skin and eyes. After skin contact wash with soap and water. This product should not cause any health problems when used in the applications suggested and the guidance provided in the safety data sheet (SDS) is followed.