

DIVYOL FLUSHING OIL

Applications:

Divyol Flushing Oil is a highly refined blend of high flash, low viscosity mineral oil and super cleanser additives recommended for use in industrial gearboxes, hydraulic systems, car engine compartments and DG sets. In this flushing process, a clean fluid circulates through the system effectively removing carbon build up, soot, dust, water, chemical contaminants and particulate matter from the equipment.

Advantages:

Divyol Flushing Oil demonstrates excellent cleaning properties. Its low viscosity enables smooth flow through the system to remove contaminants from the equipment more efficiently. After flushing, a thin film remains on the surfaces, which serves as a layer of protection against rusting of the machine/equipment during short duration storage or before commissioning of equipment. In regular usage, its efficacy results in longer oil drain intervals.

Typical properties:

Sr. No.	Characteristics	Test Method	Divyol Flushing Oil
1	Appearance	Visual	Bright and clear
2	Colour, max.	ASTM D 1500	3.0
3	Flash point, COC, °C, min.	ASTM D 92	150
4	Kinematic viscosity at 40 °C, cSt, min.	ASTM D 445	20 – 25

The above properties are typical values and do not constitute specification of the product.

Disclaimer: Gandhar makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.