

# DIVYOL GONDOLA X2 AND X3 API TC / JASO FC

## Outboard Motor Oils

### Applications

Divyol Gondola X2 and X3 are lubrication oils for use in marine environments. The blend is specially formulated for two stroke outboard gasoline engines operating within strict tolerances. It is ideal for use in high speed, high load and high engine temperature conditions. It is suitable for use in both pre-mix and injection systems.

### Specifications

Divyol Gondola X2 and X3 outboard motor oils is compatible with two stroke engine oils for engines of Japanese origin. It meets and exceeds specifications of leading outboard and personal watercraft manufacturers and also conforms to performance levels API TC and JASO FC.

### Pack Sizes

500 ml, 1 L, 5 L, 20 L, 50 L, 210 L.

### Advantages

Divyol Gondola X2 and X3 outboard motor oils have low ash detergent additives that provide protection against scuffing and wear. They provide effective protection to the engine in harsh marine environments and help extend the service life of the engine with clean burning, thus maximizing watercraft performance.

Sr. No.	Characteristics	Test Method	UOM	Specifications	
				Gondola X2	Gondola X3
1	Appearance	Visual	-	Bright and clear	Bright and clear
2	Colour, max.	ASTM D 1500	-	Greenish	Blue
3	Specific gravity at 29.5 °C	ASTM D 1298	-	To report	To report
4	Kinematic viscosity at 40 °C	ASTM D 445	cSt	60 – 75	48 – 52
5	Flash point, min. COC	ASTM D 92	°C	50	140
6	Pour point, max.	ASTM D 97	°C	-3	-3

Disclaimer: Gandhar makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.

Storage: All packages should be stored under cover. Avoid direct sun light or heat. Keep the container in closed / properly sealed condition to avoid contamination.

Handling, Health & safety: As with all the products, please take care to avoid environmental contamination when disposing of this product. Do not dispose the used oil to soil, drains and water. Avoid contact with skin and eyes. After skin contact wash with soap and water. This product should not cause any health problems when used in the applications suggested and the guidance provided in the safety data sheet (SDS) is followed.